

Datasheet

RS Pro DIN Rail Enclosure, Polycarbonate, Polystyrene, 110 x 75 x 50mm

RS Stock No: **507-680**



Product Details

RS Pro DIN rail enclosure measures 110 x 75 x 50 mm and has polycarbonate, polystyrene construction for added durability. This IP 40 rated device operates at a temperature range of -10 to +80°C. It includes upper part with 12 screw terminals and lower part with PCB integral support.

Features and Benefits

- 2-part, clip-together box which can be fitted to a DIN rail which conforms to the requirements of EN50022 or wall mounted with 2 screws
- Upper part contains 12 screw terminals rated up to 10A (max cable dia. 2.5 mm)
- Lower part has integral support for PCBs up to 2 mm thick
- Operating temperature range: -10 to +80°C
- IP40 rated

Specifications:

Body Material	PC, PS
Enclosure Rating	IP40
Internal Mounting Type	PCB Mounted
Special Features	Plug In
Standards Met	EN 50022; RoHS Compliant
Terminal Type	Screw
Dimensions	110 x 75 x 50 mm
Height	50 mm
Length	110 mm
Maximum Operating Temperature	+80°C
Maximum Terminals	12
Minimum Operating Temperature	-10°C
Width	75 mm
Enclosure Type	DIN Rail