

ADM250X-HV Voltage Signal Converter 21 20 19 RZ 🚳 ® RS AMELEC INPUT1 SUPPLY OUTPUT SCN L(+)N(-) **INPUT** OUTPUT SUPPLY

4 - 20mA dc

Load: 1200 ohms max

24Vdc +/-1.5v

100mA max

ZERO / SPAN ADJUSTMENT +/-20% OF INPUT SPAN.

DIMENSIONS: 152w X 81h X 137d (mm)

(@ 100Hz)

ACCURACY: < +/- 0.5%

Impedance: 10M ohms

0 - 1000V AC

ISOLATION (2Kv); INPUT / OUTPUT / SUPPLY / EARTH.

MOUNTING: DIN Rail (TS35)

FUNCTION: 4-20mA Output to represent 0-1000Vac input Voltage range

Attention!

The above product is based on tried and tested design techniques and meets the requirements of the relevant standards and directives.

The attention of the specifier, purchaser, installer, or the user is drawn to special measures and limitations to use, which must be observed when these products are placed into service to maintain compliance with the relevant applicable standards and directive. It is assumed that a competent person will handle the product that the standard industry practices will be applied. For further details and technical support please contact our technical sales team on telephone number shown below.

Tel: 01908-567003 E-Mail: sales@amelec-uk.com www.amelec-uk.com Fax: 01908-566735

Unit 5 Cochran Close, Crownhill, Milton Keynes

MK8 0AJ.

Issue: 19T4652 / 08.19