

AEC142 Resistance / Slidewire Trip Amplifier

- Suitable for High-Low, High-High, Low-Low or Low-High Trip combinations
- True universal AC/DC supply voltage 21V through 265V AC/DC

Technical Specifications

Input

Resistance/ Slidewire/ Thermistor/ Potentiometer Input ranges up to $20K\Omega$.

2 x Independent Relay Outputs

Each Trip relay provides a changeover contact output, rated at 250V AC 2A, 120V AC 1A (24Vdc 2A). Green LED relay / Trip status indicators. Trip points are set by 15-turn blindest potentiometers, with a Test Point (SP) to monitor each trip Set Point; 0-100% = 0.2 to 1Vdc, referenced to input 0V. Trip Hysteresis set by 15-turn potentiometers (1 to 4%).

Jumper Setting;

User friendly DIL switch / Jumper links to change original factory settings.

- 1. Relay output: N/C or N/O
- 2. Input O/C fault: Failsafe or non-failsafe
- 3. Trip on High/rising or Low/falling signal
- 4. Relay normally Energised or De-energised

Supply

Burden on supply 2W

Isolation

1000V RMS Input/Contacts/Contacts/Supply

Environmental Conditions

Storage Temperature: -20°C to +70°C Operating Ambient: 0°C to +55°C Relative Humidity: 5% to 95% RH

Relative Humidity: 5% to 95% RH (Non-Condensing) EMC: 2014/30/EU, EN 61326-1:2013 (Controlled EM)

<u>Dimensions</u>

H: 75mm W:22.5mm D:105mm

COM -N/O or N/C COM N/O or N/C -SPO TRIP CH-1 ⊕ SET ⊕ Hys AMELEC → Hys CH-2 ⊖ SET SPO TRIP Supply -Ve N +Ve L Vdc Vac POWER SUPPLY OUTPUT1 INPUT **OUTPUT2**

WIRING

Output 2


Output 1

Tel: 01908-567003 Email: sales@amelec-uk.com Visit: www.amelec-uk.com Fax: 01908-566735

AMELEC Instruments, Cochran Close, Crownhill, Milton Keynes, MK8 0AJ



AEC142 AC/DC Resistance Trip Amplifier



Above picture showing default setting

TRIP 1 / CH-1

Trip mode High or Low	S1	LO	HI
	1	OFF	ON
	2	ON	OFF
	3	ON	OFF
	4	OFF	ON

Relay contacts Normally	S2	NO	NC
open or closed.			

Input open / short circuit response. Failsafe or non failsafe.	53	I/P O/C	I/P S/C	I/P O/C +S/C
	1	OFF	ON	ON
	2	ON	OFF	ON

Led energise on trip or de- energise.	S4	N- ON	N- OFF
	1	ON	OFF
	2	OFF	ON

Relay energise on trip or de-energise.	S4	N- ENG	N-DE ENG
	3	ON	OFF
	4	OFF	ON

TRIP 2 / CH-2

S5	LO	HI
1	OFF	ON
2	ON	OFF
3	ON	OFF
4	OFF	ON

S6	NO	NC

S7	N- ON	N- OFF
1	ON	OFF
2	OFF	ON

	S7	N- ENG	N-DE ENG
	3	ON	OFF
ı	4	OFF	ON

Tel: 01908-567003 Email: sales@amelec-uk.com Visit: www.amelec-uk.com Fax: 01908-566735

AMELEC Instruments, Cochran Close, Crownhill, Milton Keynes, MK8 0AJ